

# PT40

The PT40 is a full-featured telematics device engineered with the latest cellular technology to meet both advanced and basic telematics needs. The PT40 is ideal for sophisticated applications that require engine data and/or connection to external devices and sensors via inputs, outputs, and serial communication.



## Key Features

- Cellular LTE CATM1/NB connectivity
- Integrated GPS engine and antenna
- J1939, J1708/J1587 and OBD-II (CAN) compliant interfaces
- OTA (Over-The-Air) Firmware Updates
- Three status LEDs
- Large capacity storage for offline operations
- Bluetooth Low Energy (BLE) for HOS, etc.
- 3-axis accelerometer for driving behavior and motion detection
- Battery backup
- Store >50,000 events

## Technical Specifications

### Physical

**Dimensions:** 85 mm x 65 mm x 20 mm  
**Weight:** 2.8 oz

### Certifications

FCC  
ISED (Canada)  
PTCRB  
AT&T  
Verizon

### Electrical Specifications

**Operating voltage:** 6V to 32V  
**Over-voltage and over-current Protected**  
**Power Consumption:** Engine On: 50mA  
Engine Off: 15 mA  
Engine On (message transmit): 100 mA

### Environmental

**Temperature:** -30°C to +65°C  
**Humidity:** 20% to 90% (non-condensing)  
**Shock and Vibration:** U.S. Military Standards J1708/J1587

### Input/Output

- 4 inputs (up to 32V)
- 2 open-drain outputs
- 1-Wire™ interface for identification buttons or temperature
- USB-C port for HOS tethering and device provisioning
- UART TX/RX



[www.rastrac.com](http://www.rastrac.com)

[sales@rastrac.com](mailto:sales@rastrac.com)

(877) 680-1188

©2020 Manning NavComp, Inc. All rights reserved. Rastrac is a registered trademark of Manning NavComp, Inc. All other trademarks are the property of their respective owners. The PT40 is a product of Pacific Track.